


PART NUMBER	LED COLOR	"A" DIMENSION	"B" DIMENSION	CUSTOMER P/N REF.
551-0001-875	GREEN DIFFUSED	.018	.118±.010	4061100
551-0001-876	YELLOW DIFFUSED	.018	.118±.010	4061102
551-0001-877	RED/GREEN BI-COLOR	.020	.118±.010	4061105

REV.	ECN NO.	REVISIONS	DRN.	CKD.	APP.	DATE
A	—	NEW RELEASE	DC		N.O.	7-25-95
B	—	.XXX TOLERANCE CHANGED TO ±.010; ADDED MATERIAL "VALOX" TO HOUSING.	DC		N.O.	8-22-95
C	—	DELETED REVERSE VOLTAGE SPEC. NOT APPLICABLE ON A 2 LEADED BI-COLOR LED.	TC		N.O.	5-11-98
D	—	REVISED GREEN AND YELLOW LED SPECS.; ADDED NOTE 2; "B" DIMENSION .118 ±.010 WAS .115 ±.010.	TC		N.O.	



NOTES:

- PACKAGE 100 PC'S PER 4"×5" ANTISTATIC AUTOBAG WITH P/N, QTY, DATE CODE AND MFG PRINTED ON BAG. PLACE 5 BAGS OF 100 PC'S EACH INTO AN APPROPRIATE SIZE ANTISTATIC ZIP LOCK BAG WITH APPROPRIATE BAR CODE LABEL. IN BAR CODE & HUMAN READABLE FORMAT: CUSTOMER P/N; DIALIGHT P/N; P.O. NUMBER; QTY PER BAG; DATE CODE. THE BAR CODE LABEL TO BE APPLIED TO BAG AND INNER CARTON. REFERENCE: CUSTOMER SPEC.: OP012.
- DIALIGHT PART NUMBER: 551-0001-875, -876, -877.

RECOMMENDED P.C. BOARD HOLE PATTERN

SINGLE-COLOR LED
OPERATING CHARACTERISTICS AT T_A = 25°C

SYMBOL	PARAMETER	COLOR	MIN	TYP	MAX	UNITS	TEST COND.
V _F	FORWARD VOLTAGE	YELLOW		2.1	2.8	V	I _F = 20 mA
		GREEN		2.1	2.8		
λ _D	PEAK WAVELENGTH	YELLOW		585		nm	
		GREEN		565			
I _V	LUMINOUS INTENSITY	YELLOW	7.4	10.0		mcd	I _F = 10 mA
		GREEN	4.7	12.6			
V _R	REVERSE VOLTAGE	ALL	5			V	I _R = 100 μA

RED/GRN BI-COLOR LED
OPERATING CHARACTERISTICS AT T_A = 25°C

SYMBOL	PARAMETER	COLOR	MIN	TYP	MAX	UNITS	TEST COND.
V _F	FORWARD VOLTAGE	RED		1.8	2.4	V	I _F = 20 mA
		GREEN		2.1	2.8		
λ _D	PEAK WAVELENGTH	RED		660		nm	
		GREEN		565			
I _V	LUMINOUS INTENSITY	RED	3.7	12.6		mcd	I _F = 20 mA
		GREEN	1.1	3.7			

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT.		
SCALE 6:1	DRAWING NUMBER	REV
ALL DIM'S IN: INCHES	C-15999	D
TOLERANCES: UNLESS OTHERWISE SPECIFIED	TITLE	
FRACTIONS: ±1/64	MATERIAL	
DECIMALS (.XX): ±.020		
DECIMALS (.XXX): ±.015		
ANGLES: ±3°		
FINISH:		
FSCM 83330	Dialight	1913 ATLANTIC AVE. MANASQUAN, N.J. 08736
	SHEET OF	FAMILY TABLE:

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Dialight:

[551-0001-875F](#) [551-0001-877F](#) [551-0001-876F](#)